

●BKT製トラクタータイヤ ラジアル・チューブレス諸元表

パタン	サイズ	荷重/速度コード	TT/TL	互換サイズ	適応リム	タイヤ幅	タイヤ外径	適用バルブ	空気圧 Kg/cm2
RT-855	250/85R20	116A8/116B	TL	9.5R20	W8(W7,W9)	250	940	TR618A	1.6
RT-855	280/85R20	112A8/B	TL	11.2R20	W10(W9)	292	984	TR618A	1.6
RT-855	250/85R22	113A8/B	TL	9.5R22	W7/W8	251	985	TR618A	1.6
RT-855	210/90R24 ◎	107A8/B	TL	8.3R24	W7	214	1,010	TR618A	1.6
RT-855	250/85R24	109A8/109B	TL	9.5R24	W8(W7,W9)	250	1,036	TR618A	1.6
RT-855	250/85R28	112A8/B	TL	9.5R28	W8	251	1,137	TR618A	1.6
RT-855	280/85R24	115A8/112B	TL	11.2R24	W10(W9)	292	1,086	TR618A	1.6
RT-855	320/85R20	119A8/B	TL	12.4R20	W11	329	1,052	TR618A	1.6
RT-855	320/85R24	122A8/119B	TL	12.4R24	W11(W9,W10)	329	1,154	TR618A	1.6
RT-855	340/85R24	125A8/122B	TL	13.6R24	W12(W11)	353	1,188	TR618A	1.6
RT-855	380/85R24	131A8/128B	TL	14.9R24	W12(W11,W13)	380	1,256	TR618A	1.6
RT-855	420/85R24	137A8/137B	TL	16.9R24	W15(W13,W14)	438	1,324	TR618A	1.6
RT-855	280/85R28	118A8/115B	TL	11.2R28	W10(W9)	292	1,187	TR618A	1.6
RT-855	320/85R28	124A8/121B	TL	12.4R28	W11(W9,W10)	329	1,256	TR618A	1.6
RT-855	340/85R28	127A8/124B	TL	13.6R28	W12(W11)	353	1,289	TR618A	1.6
RT-855	380/85R28	133A8/130B	TL	14.9R28	W12(W11,W13)	380	1,357	TR618A	1.6
RT-855	420/85R28	139A8/136B	TL	16.9R28	W15(W13,W14)	438	1,425	TR618A	1.6
RT-855	420/85R30	140A8/137B	TL	16.9R30	W15(W13,W14)	438	1,475	TR618A	1.6
RT-855	460/85R30	145A8/142B	TL	18.4R30	W16(W14,W15)	475	1,544	TR618A	1.6
RT-855	320/85R32	126A8/123B	TL	12.4R32	W11(W9,W10)	329	1,357	TR618A	1.6
RT-855	420/85R34	140A8/137B	TL	16.9R34	W11(W9,W10)	438	1,578	TR618A	1.6
RT-855	460/85R34	147A8/144B	TL	18.4R34	W16(W14,W15)	475	1,646	TR618A	1.6
RT-855	320/85R36	128A8/125B	TL	12.4R36	W11(W9,W10)	329	1,458	TR618A	1.6
RT-855	340/85R36	132A8/129B	TL	13.6R36	W12(W11)	353	1,492	TR618A	1.6
RT-855	320/85R38	143A8/B	TL	12.4R38	W10(W9.W11.DW11)	319	1,509	TR618A	1.6
RT-855	340/85R38	1433A8/130B	TL	13.6R38	W12(W11)	353	1,543	TR618A	1.6
RT-855	420/85R38	144A8/141B	TL	16.9R38	W15(W13,W14)	438	1,679	TR618A	1.6
RT-855	460/85R38	149A8/146B	TL	18.4R38	W16(W14,W15)	475	1,747	TR618A	1.6
RT-855	520/85R38	155A8/152B	TL	20.8R38	W16(W18)	516	1,849	TR618A	1.6
パタン	サイズ	荷重/速度コード	TT/TL	互換サイズ	適応リム	タイヤ幅	タイヤ外径	適用バルブ	空気圧 Kg/cm2
RT-765	260/70R20 ※	113A8/113B	TL	6.50R20	W8(W9)	258	872	TR618A	1.6
RT-765	280/70R20 ※	116A8/116B	TL	8.3R20	W9(W10)	282	900	TR618A	1.6
RT-765	360/70R20 ※	129A8/B	TL	12.4R20	W11	357	1,042	TR618A	1.6
RT-765	380/70R20 ※	132A8/132B	TL	13.6R20	W12(W11,W13)	380	1,082	TR618A	1.6
RT-765	320/70R24	116A8/116B	TL	11.2R24	W10(W9,W11)	319	1,094	TR618A	1.6
RT-765	360/70R24	122A8/122B	TL	12.4R24	W11(W10,W12)	357	1,152	TR618A	1.6
RT-765	380/70R24	125A8/125B	TL	13.6R24	W12(W11,W13)	380	1,190	TR618A	1.6
RT-765	420/70R24	130A8/130B	TL	14.9R24	W13(W12,W14L)	418	1,284	TR618A	1.6
RT-765	480/70R24	138A8/138B	TL	16.9R24	W15L(W14L,W16L)	479	1,316	TR618A	1.6
RT-765	360/70R28	125A8/125B	TL	12.4R28	W11(W10,W12)	357	1,251	TR618A	1.6
RT-765	380/70R28	127A8/127B	TL	13.6R28	W12(W11,W13)	380	1,293	TR618A	1.6
RT-765	420/70R28	133A8/133B	TL	14.9R28	W13(W12,W14L)	418	1,349	TR618A	1.6
RT-765	480/70R28	140A8/140B	TL	16.9R28	W15L(W14L,W16L)	479	1,421	TR618A	1.6
RT-765	420/70R30	134A8/134B	TL	14.9R30	W13(W12,W14L)	418	1,398	TR618A	1.6
RT-765	480/70R30	141A8/141B	TL	16.9R30	W15L(W14L,W16L)	479	1,478	TR618A	1.6
RT-765	480/70R34	149A8/149B	TL	16.9R34	W15L(W14L,W16L)	479	1,580	TR618A	1.6
RT-765	600/70R30 ※	152A8/152B	TL	16.9R34	DW20B,DW18L(W18L)	591	1,602	TR618A	1.6
RT-765	520/70R34 ※	148A8/148B	TL	18.4R34	W16L(W15L,W18L)	516	1,640	TR618A	1.6
RT-765	480/70R38	145A8/145B	TL	16.9R38	W15L(W14L,W16L)	479	1,681	TR618A	1.6
RT-765	520/70R38	150A8/150B	TL	18.4R38	W16(W15L,W18L)	516	1,749	TR618A	1.6
RT-765	580/70R38	155A8/155B	TL	20.8R38	W18L	577	1,827	TR618A	1.6
RT-765	710/70R38	178A8/175B	TL		DW23A	716	1,959	TR618A	1.6
RT-765	620/70R42 ※	160A8/160B	TL	20.8R42	DW20A	625	1,935	TR618A	1.6
RT-765	710/70R42 ※	173A8/B	TL		DW23A	716	2,061	TR618A	1.6
パタン	サイズ	荷重/速度コード	TT/TL	互換サイズ	適応リム	タイヤ幅	タイヤ外径	適用バルブ	空気圧 Kg/cm2
RT-657	440/65R24 ※	135D/138A8	TL	13.6R24	W14L(W13,W15L)	441	1182	TR618A	1.6
RT-657	480/65R24	140D/143A8	TL	14.9R24	W15L(W14L)	479	1234	TR618A	1.6
RT-657	540/65R24	146D/149A8	TL	16.9R24	W16L(W18L)	530	1312	TR618A	1.6
RT-657	440/65R28 ※	138D/141A8	TL	13.6R28	W14L(W13,W15L)	441	1283	TR618A	1.6
RT-657	480/65R28	142D/145A8	TL	14.9R28	W15L(W14L)	479	1335	TR618A	1.6
RT-657	540/65R28	149D/152A8	TL	16.9R28	W16L(W18L)	530	1413	TR618A	1.6
RT-657	540/65R30	150D/153A8	TL	16.9R30	W16L(W18L)	530	1464	TR618A	1.6
RT-657	600/65R28	154D/157A8	TL	16.9R30	DW20B(W18L)	611	1491	TR618A	1.6
RT-657	600/65R30 ※	155D/158A8	TL	18.4R30	DW20B(W18L)	611	1542	TR618A	1.6
RT-657	540/65R34 ※	152D/155A8	TL	16.9R34	W16L(W18L)	530	1556	TR618A	1.6
RT-657	600/65R34 ※	157D/160A8	TL	18.4R34	DW20B(W18L)	611	1644	TR618A	1.6
RT-657	540/65R38	153D/156A8	TL	16.9R38	W16L(W18L)	530	1667	TR618A	1.6
RT-657	600/65R38	159D/162A8	TL	18.4R38	DW20B(W18L)	611	1745	TR618A	1.6
RT-657	650/65R38	163D/166A8	TL	20.8R38	DW20B	645	1811	TR618A	1.6
RT-657	650/65R42	165D/168A8	TL	20.8R42	DW20B	645	1913	TR618A	1.6
パタン	サイズ	荷重/速度コード	TT/TL	互換サイズ	適応リム	タイヤ幅	タイヤ外径	適用バルブ	空気圧 Kg/cm2
RT-955	210/90R24	107A8/B	TL	8.3R24	W7	214	1010	TR618A	1.6
RT-955	210/95R28	116A8/B	TL	8.3R28	W7	214	1111	TR618A	1.6
RT-955	230/95R32	128A8/B	TL	9.5R32	W8	238	1251	TR618A	1.6
RT-955	230/95R36	130A8/B	TL	9.5R36	W8	238	1352	TR618A	1.6
RT-955	230/95R44	134A8/B	TL	9.5R44	W8	238	1556	TR618A	1.6
RT-955	300/95R46	148A8/B	TL	12.4R46	W9	295	1738	TR618A	3.6